

MINI 15 AC W.

110mm x 45mm x 151mm




1 x G9 Bulb retrofit
led 3,8 W Code 2990
470 lumens | 2.700K | CRI 80



2 x DOB LED 5W
2x 500 lumens | 2.700K | CRI 90
3-step MacAdam
PF. 0,95

Class I: Basic insulation



MINI 5 AC W.

110mm x 45mm x 51mm



1 x G9 Bulb retrofit
led 3,8 W Code 2990
470 lumens | 2.700K | CRI 80



2 x DOB LED 5W
2x 500 lumens | 2.700K | CRI 90
3-step MacAdam
PF. 0,95

Class I: Basic insulation

Finishes

- 6019 ● Metallic gray lacquering (similar to 9006 matt)
- 1019 ● Matt white lacquering (RAL 9016)
- 4019 ● Matt black lacquering (RAL 9005)
- 3273 ● Metallic gray lacquering (similar to 9006 matt)
- 4273 ● Matt white lacquering (RAL 9016)
- 5273 ● Matt black lacquering (RAL 9005)

Finishes

- 6020 ● Metallic gray lacquering (similar to 9006 matt)
- 1020 ● Matt white lacquering (RAL 9016)
- 4020 ● Matt black lacquering (RAL 9005)
- 3274 ● Metallic gray lacquering (similar to 9006 matt)
- 4274 ● Matt white lacquering (RAL 9016)
- 5274 ● Matt black lacquering (RAL 9005)

DOWNLOADS

Catalogue

[Mini](#)

3Ds Files

[5273/6019](#)
[1019/3273](#)
[4019/4273](#)

3Ds Max Files

[5273/6019](#)
[1019/3273](#)
[4019/4273](#)

Assembly instructions

[4274/6020](#)
[1020/3274](#)
[4020/4274](#)
[6019/3273](#)
[6020/3274](#)

Photometric curve

[6019/1019/4019](#)
[3273/4273/5273](#)
[6020/1020/4020](#)
[3274/4274/5274](#)

Economic efficiency index

[6019/1019/4019](#)
[3273/4273/5273](#)
[6020/1020/4020](#)
[3274/4274/5274](#)

Minimal expression,
light impact

Decorative base and rear- base for both LED location and wall mounting, injected in aluminium. . Finishing in

metallic grey lacquering (similar to 9006 matt) matt white lacquer (RAL 9016) and matt black lacquer (RAL 9005).