



F0095023 Blue Steel Anodized

### Aim Small

Designed by Ronan & Erwan Bouroullec, 2014


12W - 725lm - 2700K - CRI> 90



Suspended light fitting. Body in varnished aluminium sheet, shade in photo-etched optical polycarbonate. Internal reflector in photo-etched PC. Directionable body. Powered directly from mains. The LED can be dimmed with a «Triac for Led» dimmer approved by Flos. Flos does not respond in case of wrong electrical connection system installations. The cable has a useful length of 9 metres and thus the lamp can be suspended 3 metres from the ceiling. Multiple rose with capacity to connect up to 5 Aim Small also available.

Are you a professional and your project needs consulting and support?

**BOOK AN APPOINTMENT** 



## Main specifications

| EAN               | 8059607013519       |
|-------------------|---------------------|
| Mounting          | Suspension          |
| Enviroment        | Indoor dry location |
| Light source type | LED                 |
| LED type          | LED Module          |
| Lamp holder       | LED Module          |
| Number of heads   | 1                   |
| Power (W)         | 12                  |
| System power (W)  | 12                  |
| System flux (lm)  | 725                 |

### **Physical**

| Colour              | Blue Steel Anodized |
|---------------------|---------------------|
| Cord length (mm)    | 9000/3000           |
| Net weight (kg)     | 1.35                |
| Package height (cm) | 31                  |
| Package width (cm)  | 30                  |
| Package length (cm) | 30                  |
| Package volume (m3) | 0.03                |
| IP                  | 20                  |
| IP external         | 20                  |

| Downlo | oad |
|--------|-----|
|--------|-----|

| ounting instructions | <b>↓</b> PDF |
|----------------------|--------------|
| are Parts            | <b>₩</b> PDF |

## Photometric Files

LDT / IES

Spare Parts

<u>↓</u> LDT

## **Technical Drawings**

| 2D | <b>⊥</b> ZIP |
|----|--------------|
| 3D | <b>⊥</b> ZIP |

















https://professional.flos.com/en/global/product/aim-small-f0095023/

F0095023

## Schematic light drawing



Luminous flux luminaire 725 lm

The above drawing is for illustrative purposes only and refers to product code: F00950XXWAIM-SMALL\_12W-LED

# Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class F



Replaceable (LED only) light source by a professional


#### **Photometric**

| Lighting type      | Direct         |
|--------------------|----------------|
| Light distribution | Roto symmetric |
| CCT (K)            | 2700           |
| CRI>               | 90             |

#### **Electrical**

| Insulation class   | II                |
|--------------------|-------------------|
| Frequency (Hz)     | 50/60             |
| Main voltage (Vac) | 220-240           |
| Driver             | Integrated        |
| Dimming type       | Mains Cut Dimming |
| Cord length (mm)   | 9000/3000         |
| Batteries inside   | No                |

# Accessories & Power Supply



https://professional.flos.com/en/global/product/aim-small-f0095023/

F0095023

## **Spare Parts**









RF0090123

Dark grey/steel blue ceiling attachment assembly

RF0095100

Sink/chip led/reflector assembly Aim small RF0095500

Aim small opal diffuser

RF06750

Kit of quantity 3 m4 screws



RF1555030

Ceiling rose assembly