

Arrangements Round Medium

F0407030 - Black

Designed by Michael Anastassiades

Diffuse light suspended lighting device. Body in extruded, curved NC-machined and black powder-coated aluminium, diffuser in platinum optical silicone.

Each component can be connected to the power pack by means of an electrical and mechanical connection system designed for customisable product set-up.

Roses available with two powers: lamp with power under 70W and lamp with power under 190W. Class III roses also available for installations with remote power supply: "surface" version for installations on cement, "recessed" version for plasterboard ceilings.

The electronics integrated in the rose enables use of dimming systems: push, 1-10, potentiometer, DALI. In the absence of these systems, the light flow can be set with the push system included in the rose. Cable length 2.4m

ø 665 mm

RG 0

Main	spe	citica	ations

Mounting Environment Light source type Light source replaceable

LED type

Optical Lighting Type

CCT (K)

System Flux (Im)

Lighting distribution

Cold Beam Lighting


Extreme Cut off

Suspension In door dry location LED Replaceable (LED on ly) light source by a profession al LED Module 1770 Lamp holder Dimmable Autoprotected Lamp Number of heads Source Power (W)

LED Module
Yes
No
1
35

Indirect, Direct Symmetric 2700K No No





Electrical			
Insulation class		Batteries Inside	No
Frequency (Hz) Main Voltage (Vac) Driver	50/60 48 Remote	Dimming Interface	Remote Dimmable (Dimmer Not
Dimmable	Yes	.	Included)
		Cord length (mm) Charging Min Time	2500 N o
Physical			
Colour	Black		
Net weight (kg)	0.75		
Gross weight (kg)	1.65		
IP	20		
IP external	20		

Arrangements Round Medium



F0415030

Rose F0418030 F0416030