

### Belt Brown Casambi 2000mm

No

03.8530.18.CB - Deep Brown

Designed by Ronan & Erwan Bouroullec

This iconic profile for suspended installation features a refined leather surface developed specifically for Flos. Belt is pure flexibility, a sinuous line that creates a balance between the softness of leather and the rigidity of aluminium. The soft part is represented by the connection to the electrical network, while the rigid parts correspond to the light source, the long lines of light. The fixture is equipped with integrated direct and indirect lighting and each light source can be controlled individually via remote control. The product is installed with the use of leather straps to hang the lighting profile, sliding the straps through dedicated metal clasps that act as hooks on the ceiling. Each strap may be regulated to match the shape of the environment. A special microconnector integrated into the terminal of the lighting profile allows for electrical connection through a simple snap. The electrical connection is hidden within the leather strap, which supports the composition. Profiles available in black, natural leather, and green finishes. Electrical system powered at 48V dimmable with CASAMBI controller integrated inside the fixture. To manage the system it is necessary to download the FLOS Control® powered by Casambi app (available on Apple Store and Google Play).

### Main specifications

<b>Mounting Environment</b>	Suspension Indoor dry location	<b>Lamp category</b>	LED
<b>Light source type</b>	LED	<b>Lamp holder</b>	LED Module
<b>Light source replaceable</b>	Non-replaceable light source	<b>Ilcos</b>	LED
<b>LED type</b>	Top LED	<b>Dimmable</b>	Yes
<b>Number of heads</b>	1	<b>Autoprotected Lamp</b>	No
<b>Source Power (W)</b>	55.5		
<b>System Power (W)</b>	55.5		
<b>System Flux (lm)</b>	1700		

### Optical

<b>Lighting Type</b>	Total
<b>Lighting distribution</b>	Sym metric
<b>CCT (K)</b>	2700K
<b>CRI&gt;</b>	95
<b>Cold Beam Lighting</b>	No
<b>Beam angle C0-180 (°)</b>	60
<b>Beam angle C90-270 (°)</b>	102
<b>Beam angle indirect C0-180 (°)</b>	60
<b>Beam angle direct C90-270 (°)</b>	102
<b>Extreme Cut off</b>	No

### Electrical

<b>Insulation class</b>	III	<b>Driver</b>	Remote included
<b>Frequency (Hz)</b>	50/60	<b>Dimmable</b>	Yes
<b>Main Voltage (Vac)</b>	220/240	<b>Dimmable type</b>	Dimmable Casambi
<b>Forward Voltage (V)</b>	48	<b>Batteries Inside</b>	No
<b>LED Voltage Vf (Vdc)</b>	48	<b>Dimming Range (%)</b>	1-100
<b>Dimming Interface</b>	Switch Integrated (Remote Dimmable)		
<b>Precabled</b>	Yes		
<b>Cord length (mm)</b>	2.5m		
<b>Emergency Type</b>	No		

### Physical

<b>Colour</b>	Deep Brown	<b>Length (mm)</b>	2000
<b>Trim</b>	No	<b>Net weight (kg)</b>	6.5
<b>Field Cuttable</b>	No	<b>IP</b>	20
<b>Orientations</b>	Fixed	<b>IP external</b>	20
<b>Recessed depth (mm)</b>	0	<b>H2O stop</b>	No

