

FLOS


F018E21K025 Terracotta

In Vitro Unplugged NEW

Designed by Philippe Starck



Lighting device for exterior ground installation. Opalescent diffuser integrated in the head and outer protective glass in transparent borosilicate. The structural parts are made of die-cast and extruded aluminium treated with a chemical conversion process to protect against atmospheric agents. The body is powder coated with a range of available finishes. Integrated LED light source with Edge Lighting technology to guarantee perfectly uniform lighting. Portable version equipped with handle for transport. Dimmer driver 5/100-240 V/50-60 Hz integrated into the body of the device with optical touch sensor on the head to regulate the brightness in 4 steps: 100% - 50% - 3% - OFF. Rechargeable via micro USB-C cable, 120 cm long, guaranteeing continuous lighting up to 6 hours. IP20 charger with EUR, UK, USA interchangeable plugs.



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

Main specifications

Mounting	Table
Environment	Outdoor wet location
LED type	Edge Lighting
Lamp category	LED
Power (W)	2.5W
System flux (lm)	115

Physical

Colour	Terracotta
Trim	No
Orientation	Fixed
Net weight (kg)	1
IP	65

Download


Mounting instructions	ZIP
Mounting instructions	ZIP

Photometric Files


LDT / IES	ZIP
-----------	---------------------

Technical Drawings

2D	ZIP
3D	ZIP



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
Beam angle C0-180 (°)	106
Beam angle C90-270 (°)	106

Electrical

Insulation class	III
Frequency (Hz)	50-60
Main voltage (Vac)	5/100÷240V
Driver	Integrated
Dimmable	Yes
Dimming type	Dimmer on board
Emergency type	No

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class F



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Notes

When setting up and maintaining the device, be particularly careful not to damage the powder coating.
Damage combined with water may lead to corrosion.
Chemical products may damage the corrosion protection.